

### Product designation

**Lightbar 60 Evolution**

Article no. 32.351.XX

### Product description

Light with dimensions 58 x 12 cm (22.8 x 4.7 inches), can be operated at up to 1 x 3200 J, "tunnel-shaped" plexiglass diffuser, sheet steel back with cable outlet, 5 meter (16.4 ft) cable, modelling light switch, and separate interchangeable tilt head.

### Scope of delivery

Lightbar with one cable, flash tubes, modelling lamps and interchangeable tilt head.

### Technical data

Flash energy		1 x 3200 J
F-stop at 2 m (6 ½ ft), 100 ISO		32 5/10
Modelling light	220 V	10 x 20 W / 24 V
	110 V	10 x 20 W / 12 V
Cable length		1 x 5 m (16.4 ft.)
Cooling		1 fan
Dimensions		58 x 12 x 13 cm / 22.8 x 4.7 x 5.1 inches
Weight		3.6 kg / 8 lb

### Compatibility

Power packs	Grafit 2, 4, A2, A4, A2 RFS, A4 RFS, A8 RFS, A2 plus, A4 plus, Topas A2, A4, A8 Nano 2, Mobil, Mobil A2 R Pulso 2, A2, 4, A4, Opus 2, A2, 4, A4, A8, Primo, Primo A, Primo A fashion, Primo 4,
-------------	--

For heat-related reasons, it is not possible to equip the Lightbar with a proportional halogen modelling lamp matching the other lamps.

### Accessories

- Art. no. 33.272.00 Plexi cap mat for Lightbar 60 Evolution
- Art. no. 33.228.00 Barn door for Lightbar/Striplite 60 Evolution
- Art. no. 33.274.00 Striplite adapter for Lightbar 60 Evolution
- Art. no. 33.217.00 Honeycomb grid for Striplite 60 Evolution

### **Application**

Background gradations and general gradations - Automobile and bus lighting - Mirror projection of lines - Outlining contours and edges - Deep objects (depth) as in cupboards, deep-freezers, car boots etc. can be lit in the simplest way - Several Lightbars can be placed together for uninterrupted lighting - Simple and versatile mounting with the interchangeable tilt head - The possibility of transforming the Lightbar into a Striplite increases the application range.